NSN 5305-01-530-2440

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-530-2440 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.276 inches **Fastener Length:** Between 0.386 inches and 0.416 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.105 inches and 0.115 inches **Spline Major Diameter:** 0.155 inches **Grip Diameter:** Between 0.163 inches and 0.164 inches **Internal Drive Style:** Torx **Thread Diameter:** 0.164 inches **Grip Length:** 0.125 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 2240 pounds per square inch Material: Stainless steel **Material Specification:** A286 assn standard single material response **Surface Treatment:** Passivate or cadmium **Surface Treatment Specification:** Ams-qq-p-35 federal specification single treatment response or ams-qq-p-46, type 2, class 2 federal specification single treatment response **Thread Series Designator:** Unjc Shelf Life:

N/a

Unit Of Measure:

NSN 5305-01-530-2440

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0