Externally Relieved Body Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-530-5972

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.795 inches and 0.805 inches
Fastener Length:
Between 1.110 inches and 1.140 inches
Head Style:
Pan
Head Diameter:
Between 0.205 inches and 0.219 inches
Head Height:
Between 0.070 inches and 0.080 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.112 inches
Thready Qty Per Inch (tpi):
40
Externally Relieved Body Diameter Quantity:
1
Product Name:
Screw, machine, captive
Color:
Black
Material:
Steel comp 314 or steel comp 316 or steel comp 317 or steel comp 321 or steel comp 322
Material Specification:
Qq-s-763 federal standard single material response
Surface Treatment:
Oxide
Surface Treatment Specification:
Mil-c-13924, class 4 military specification single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Externally Relieved Body Screw - Page 2 of 2



**Fiig:** A003b0

Mil-std (military Standard):

Mil-c-13924 spec.