NSN 5305-01-530-5972

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-530-5972 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.795 inches and 0.805 inches **Fastener Length:** Between 1.110 inches and 1.140 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.080 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Product Name:** Screw, machine, captive Color: Black Material: Steel comp 314 or steel comp 316 or steel comp 317 or steel comp 321 or steel comp 322 **Material Specification:** Qq-s-763 federal standard single material response **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924, class 4 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5305-01-530-5972

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.