## NSN 5305-01-530-7392



Panel Screw Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-530-7392 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.203 inches **Fastener Length:** Between 0.188 inches and 0.250 inches **Head Style:** Fillister **Head Diameter:** 0.219 inches **Head Height:** 0.110 inches **Internal Drive Style:** Hexagon **Material Accommodated Thickness:** 0.130 inches **Thread Diameter:** 0.112 inches Width Across Flats: 0.094 inches Thready Qty Per Inch (tpi): 40 **Product Name:** Captive screw, cap skt head, low profile, internal float **Special Features:** Between this has a float of 0.116 inches and 0.025 inches Material: Stainless steel **Material Specification:** Ams 5735, heat treat to 160 ksi min u.T.S. Assn standard single material response **Surface Treatment:** 

**Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjc

Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5305-01-530-7392

Panel Screw Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0