## NSN 5305-01-532-2873

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-532-2873

| Thread Class:   |
|---|
| 3a  |
| Sa<br>Thread Direction:   |
|   |
| Right-hand  |
| Thread Length:  |
| 0.316 inches  |
| Fastener Length:  |
| Between 0.882 inches and 0.897 inches   |
| Head Style:   |
| Fillister countersunk   |
| Head Diameter:  |
| 0.449 inches  |
| Head Height:  |
| 0.106 inches  |
| Spline Major Diameter:  |
| 0.221 inches  |
| Grip Diameter:  |
| Between 0.248 inches and 0.249 inches   |
| Internal Drive Style:   |
| Torx  |
| End Application:  |
| V-22  |
| Thread Diameter:  |
| 0.250 inches  |
| Grip Length:  |
| 0.250 inches  |
| Thready Qty Per Inch (tpi):   |
| 28  |
| Min. Tensile Strength (psi):  |
| 5820 pounds per square inch   |
| Countersink Angle:  |
| Between 99.0 degrees and 101.0 degrees  |
| Product Name:   |
| Screw, shear, flat 100 degrees head, close tolerance, short thread, six lobe recess, 95 ksi fsu |
| Material:   |
| Titanium  |
| Thread Series Designator:   |
| Unjf  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| -   |

## NSN 5305-01-532-2873

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

