NSN 5305-01-532-9956



Close Tolerance Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-532-9956 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.323 inches **Fastener Length:** Between 1.870 inches and 1.900 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **Grip Diameter:** Between 0.188 inches and 0.189 inches **Internal Drive Style:** Cross recess type 1 **End Application:** C130 amp cmb **Thread Diameter:** 0.190 inches **Grip Length:** Between 1.552 inches and 1.572 inches Thready Qty Per Inch (tpi): 32 **Product Name:** Bolt, pan head, close tolerance, short thread Material: Steel comp 4140 or steel comp 4340 or steel comp e4340 **Material Specification:** Mil-s-5626 military specification 1st material response or ams6415 assn standard 2nd material response or mil-s-5000 military specification 3rd material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, ty ii, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf

N/a

Shelf Life:

Unit Of Measure:

NSN 5305-01-532-9956

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.