## NSN 5305-01-533-0658



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-533-0658 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.750 inches **Fastener Length:** Between 2.234 inches and 2.281 inches **Head Style:** Hexagon **Head Height:** Between 0.080 inches and 0.093 inches Width Between Flats: Between 0.243 inches and 0.251 inches **Internal Drive Style:** Cross recess type 1 **End Application:** C130 amp cmb **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: Between 36.0 rockwell c and 40.0 rockwell c **Product Name:** Screw, hex head, cruciform recess, full thread **Screw Material:** Steel comp e4340 or steel comp 8740 **Screw Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams6322 assn standard 2nd material response **Screw Surface Treatment:** 

Cadmium and chromate

### **Screw Surface Treatment Specification:**

Qq-p-416 ty2 cl2 federal specification single treatment response

#### **Special Features:**

Undrilled head

#### **Thread Series Designator:**

Unjc

#### Shelf Life:

N/a

# NSN 5305-01-533-0658

Machine Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-5000 spec.