## NSN 5305-01-533-0658

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-533-0658



## **Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** 1.750 inches **Fastener Length:** Between 2.234 inches and 2.281 inches **Head Style:** Hexagon **Head Height:** Between 0.080 inches and 0.093 inches Width Between Flats: Between 0.243 inches and 0.251 inches **Internal Drive Style:** Cross recess type 1 **End Application:** C130 amp cmb **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: Between 36.0 rockwell c and 40.0 rockwell c **Product Name:** Screw, hex head, cruciform recess, full thread **Screw Material:** Steel comp e4340 or steel comp 8740 **Screw Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams6322 assn standard 2nd material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 ty2 cl2 federal specification single treatment response **Special Features:** Undrilled head **Thread Series Designator:** Unjc Shelf Life: N/a

## NSN 5305-01-533-0658

Machine Screw - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-5000 spec.

