NSN 5305-01-533-0878

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-533-0878 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.323 inches **Fastener Length:** Between 1.246 inches and 1.276 inches **Head Style:** Flat countersunk **Head Diameter:** 0.331 inches **Grip Diameter:** Between 0.163 inches and 0.164 inches **Internal Drive Style:** Cross recess type iii **End Application:** C130 amp cmb **Thread Diameter:** 0.164 inches **Grip Length:** Between 0.928 inches and 0.948 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Bolt, 100 degrees head, cruciform recess, close tolerance **Special Features:** Material: cres-a286 (uns s66286). Undrilled shank, plated, nonlocking. Material: Stainless steel **Material Specification:** Ams5731 assn standard 1st material response or ams5732 assn standard 2nd material response or ams5737 assn standard 3rd material response or ams5853 assn standard 4th material response **Surface Treatment:**

Unjc

Cadmium

Surface Treatment Specification:

Thread Series Designator:

Qq-p-416, type ii class 2 federal specification single treatment response

Shelf Life:

N/a

NSN 5305-01-533-0878

Close Tolerance Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0