## NSN 5305-01-533-1750

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-533-1750 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.345 inches and 0.395 inches **Fastener Length:** Between 1.105 inches and 1.135 inches **Head Style:** Pan **Head Diameter:** Between 0.473 inches and 0.492 inches **Head Height:** Between 0.162 inches and 0.175 inches **Grip Diameter:** Between 0.248 inches and 0.249 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.740 inches and 0.760 inches Thready Qty Per Inch (tpi): 28 **Special Features:** Note: chromium plate on shank only. Material: Steel comp e4340 or steel comp 8740 **Material Specification:** Mil-s-6049 military specification 1st material response or ams 6322 assn standard 2nd material response **Surface Treatment:** Cadmium or chromate **Surface Treatment Specification:** Qq-p-0416, type ii, class 2 federal specification 1st treatment response or qq-p-320, class 2 federal specification 2nd treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5305-01-533-1750

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6049 spec.