NSN 5305-01-533-4892

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-533-4892

| Thread Class: |
|--|
| |
| 3a Thread Birastians |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.365 inches |
| Fastener Length: |
| Between 1.038 inches and 1.068 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.338 inches and 0.381 inches |
| Grip Diameter: |
| Between 0.187 inches and 0.188 inches |
| Internal Drive Style: |
| Cross recess type ii |
| End Application: |
| C-135 aircraft |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| Between 0.678 inches and 0.698 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Product Name: |
| Bolt, 100degree head, cruciform recess, close tolerance |
| Material: |
| Stainless steel |
| Material Specification: |
| Ams5731 assn standard single material response or ams5737 assn standard single material response |
| Surface Treatment: |
| Aluminum |
| Surface Treatment Specification: |
| Nas4006 national std/spec single treatment response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5305-01-533-4892

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0