NSN 5305-01-534-4519

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-534-4519 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.345 inches **Fastener Length:** Between 0.892 inches and 0.922 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.372 inches and 0.381 inches **Spline Major Diameter:** Between 0.154 inches and 0.156 inches **Grip Diameter:** 0.189 inches **Point Diameter:** 0.345 inches **Point Style:** Flat **Internal Drive Style:** Torx **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.552 inches and 0.572 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Bolt, 100 degree tension head, gear drive recess Material: Nickel alloy 718 Ams 5662 assn standard single material response

Material Specification: Surface Treatment: Passivate Thread Series Designator: Unjf Shelf Life: N/a

NSN 5305-01-534-4519

Close Tolerance Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0