NSN 5305-01-535-0031

Externally Relieved Body Screw - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5305-01-535-0031 |
|---|
| Thread Class: 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.125 inches |
| Fastener Length: |
| 0.375 inches |
| Head Style: |
| Knurled no. 5 |
| Head Diameter: |
| 0.313 inches |
| Head Height: |
| 0.313 inches |
| Point Style: |
| Cone |
| Internal Drive Style: |
| Slot |
| End Application: |
| 4931-01-120-0764 direct support electronic system test set |
| Thread Diameter: |
| 0.209 inches |
| Thready Qty Per Inch (tpi): |
| 40 |
| Externally Relieved Body Diameter Quantity: |
| 1 |
| Point Chamfer Angle: |
| 90.0 degrees |
| Product Name: |
| Captive panel screw type 2 |
| Special Features: |
| Non magnetic |
| Color: |
| Natural |
| Material: |
| Stainless steel |
| Surface Treatment: |
| Passivate |
| Thread Series Designator: |
| Unc |
| Shelf Life: |

N/a

NSN 5305-01-535-0031

Externally Relieved Body Screw - Page 2 of 2



| | | | ure: | |
|--|--|--|------|--|
| | | | | |
| | | | | |

--

Demilitarization:

No

Fiig:

A003b0