## NSN 5305-01-535-1780

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-535-1780 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.316 inches **Fastener Length:** 1.191 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.449 inches and 0.507 inches **Grip Diameter:** Between 0.248 inches and 0.249 inches **Shank Unthreaded Hole Diameter:** 0.076 inches first hole **Internal Drive Style:** Offset cruciform (torque set) **End Application:** U-2 **Thread Diameter:** 0.250 inches **Grip Length:** 0.875 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Distance From Head Largest Bearing Surface To Shank Hole Center: 1.050 inches first hole and 1.090 inches first hole **Product Name:** Flat 100 degrees head, close tolerance, short thread, offset cruciform, 160ksi Material: Iron alloy 660

**Material Specification:** 

Ams5737 assn standard single material response

**Surface Treatment:** 

**Passivate** 

**Surface Treatment Specification:** 

Qq-p-35 federal specification single treatment response

## NSN 5305-01-535-1780

Close Tolerance Screw - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0