NSN 5305-01-535-8273

Close Tolerance Screw - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-535-8273

Thread Class:3aThread Direction:Right-handThread Length:0.345 inchesFastener Length:Between 1.267 inches and 1.297 inchesHead Style:Flat countersunkHead Diameter:0.337 inchesGrip Diameter:0.189 inchesInternal Drive Style:Cross recess type 1End Application:E-3a aircraftThread Diameter:0.190 inchesGrip Length:Between 0.936 inches and 0.938 inchesThready Qty Per Inch (tpi):32
Thread Direction: Right-hand Thread Length: 0.345 inches Fastener Length: Between 1.267 inches and 1.297 inches Head Style: Flat countersunk Head Diameter: 0.337 inches Grip Diameter: 0.337 inches Grip Diameter: 0.189 inches Internal Drive Style: Cross recess type 1 E-3a aircraft Thread Diameter: 0.190 inches Grip Length: Between 0.936 inches and 0.938 inches Thready Qty Per Inch (tpi):
Right-handThread Length:0.345 inchesFastener Length:Between 1.267 inches and 1.297 inchesHead Style:Flat countersunkHead Diameter:0.337 inchesGrip Diameter:0.189 inchesInternal Drive Style:Cross recess type 1End Application:E-3a aircraftThread Diameter:0.190 inchesGrip Length:Between 0.936 inches and 0.938 inchesThready Qty Per Inch (tpi):
Thread Length: 0.345 inches Fastener Length: Between 1.267 inches and 1.297 inches Head Style: Flat countersunk Head Diameter: 0.337 inches Grip Diameter: 0.337 inches Grip Diameter: 0.189 inches Internal Drive Style: Cross recess type 1 End Application: E-3a aircraft Thread Diameter: 0.190 inches Grip Length: Between 0.936 inches and 0.938 inches Thready Qty Per Inch (tpi):
0.345 inches Fastener Length: Between 1.267 inches and 1.297 inches Head Style: Flat countersunk Head Diameter: 0.337 inches Orip Diameter: 0.189 inches Internal Drive Style: Cross recess type 1 End Application: E-3a aircraft Thread Diameter: 0.190 inches Grip Length: Between 0.936 inches and 0.938 inches Thready Qty Per Inch (tpi):
Fastener Length:Between 1.267 inches and 1.297 inchesHead Style:Flat countersunkHead Diameter:0.337 inchesGrip Diameter:0.189 inchesInternal Drive Style:Cross recess type 1End Application:E-3a aircraftThread Diameter:0.190 inchesGrip Length:Between 0.936 inches and 0.938 inchesThready Qty Per Inch (tpi):
Between 1.267 inches and 1.297 inches Head Style: Flat countersunk Head Diameter: 0.337 inches Grip Diameter: 0.189 inches Internal Drive Style: Cross recess type 1 End Application: E-3a aircraft Thread Diameter: 0.190 inches Grip Length: Between 0.936 inches and 0.938 inches Thready Qty Per Inch (tpi):
Head Style:Flat countersunkHead Diameter:0.337 inchesGrip Diameter:0.189 inchesInternal Drive Style:Cross recess type 1End Application:E-3a aircraftThread Diameter:0.190 inchesGrip Length:Between 0.936 inches and 0.938 inchesThready Qty Per Inch (tpi):
Flat countersunk Head Diameter: 0.337 inches Grip Diameter: 0.189 inches Internal Drive Style: Cross recess type 1 End Application: E-3a aircraft Thread Diameter: 0.190 inches Grip Length: Between 0.936 inches and 0.938 inches Thready Qty Per Inch (tpi):
Head Diameter:0.337 inchesGrip Diameter:0.189 inchesInternal Drive Style:Cross recess type 1End Application:E-3a aircraftThread Diameter:0.190 inchesGrip Length:Between 0.936 inches and 0.938 inchesThready Qty Per Inch (tpi):
0.337 inches Grip Diameter: 0.189 inches Internal Drive Style: Cross recess type 1 End Application: E-3a aircraft Thread Diameter: 0.190 inches Grip Length: Between 0.936 inches and 0.938 inches Thready Qty Per Inch (tpi):
Grip Diameter: 0.189 inches Internal Drive Style: Cross recess type 1 End Application: E-3a aircraft Thread Diameter: 0.190 inches Grip Length: Between 0.936 inches and 0.938 inches Thready Qty Per Inch (tpi):
0.189 inches Internal Drive Style: Cross recess type 1 End Application: E-3a aircraft Thread Diameter: 0.190 inches Grip Length: Between 0.936 inches and 0.938 inches Thready Qty Per Inch (tpi):
Internal Drive Style: Cross recess type 1 End Application: E-3a aircraft Thread Diameter: 0.190 inches Grip Length: Between 0.936 inches and 0.938 inches Thready Qty Per Inch (tpi):
Cross recess type 1 End Application: E-3a aircraft Thread Diameter: 0.190 inches Grip Length: Between 0.936 inches and 0.938 inches Thready Qty Per Inch (tpi):
End Application: E-3a aircraft Thread Diameter: 0.190 inches Grip Length: Between 0.936 inches and 0.938 inches Thready Qty Per Inch (tpi):
E-3a aircraft Thread Diameter: 0.190 inches Grip Length: Between 0.936 inches and 0.938 inches Thready Qty Per Inch (tpi):
Thread Diameter: 0.190 inches Grip Length: Between 0.936 inches and 0.938 inches Thready Qty Per Inch (tpi):
0.190 inches Grip Length: Between 0.936 inches and 0.938 inches Thready Qty Per Inch (tpi):
Grip Length: Between 0.936 inches and 0.938 inches Thready Qty Per Inch (tpi):
Between 0.936 inches and 0.938 inches Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi):
32
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Product Name:
Bolt, 100 degrees head, cross recess, 95ksi shear, short thread a286
Material:
Iron alloy 660
Surface Treatment:
Passivate
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A003b0