## NSN 5305-01-536-4448



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-536-4448 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.425 inches **Fastener Length:** Between 0.6425 inches and 0.6725 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.294 inches and 0.301 inches **Shoulder Diameter:** 0.2177 inches grip and 0.2182 inches grip **Shoulder Length:** 0.2665 inches grip **Hole Diameter:** Between 0.070 inches and 0.080 inches **Spline Minor Diameter:** Between 0.1105 inches and 0.1125 inches **Spline Major Diameter:** Between 0.1540 inches and 0.1560 inches **Internal Drive Style:** Torx **End Application:** F/a 18 e/f aircraft **Thread Diameter:** 0.250 inches **Hole Quantity: Hole Type:** Drilled **Features Provided:** Cetyl alcohol lubricant Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Criticality Code Justification:** Agav **Shoulder Shape:** 

Round grip

## **NSN 5305-01-536-4448** Shoulder Screw - Page 2 of 2



Product Name:
Eddie bolt aircraft
Material:
Nickel alloy 718
Material Specification:
Ams5662 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Mil-l-87132 type 1 grade b military specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):
Mil-I-87132 spec