

View Online at <https://aerobasegroup.com/nsn/5305-01-537-3449>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.521 inches and 0.541 inches

**Fastener Length:**

1.250 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.188 inches and 0.209 inches

**Width Between Flats:**

Between 0.554 inches and 0.564 inches

**Spline Minor Diameter:**

Between 0.188 inches and 0.192 inches

**Spline Major Diameter:**

Between 0.264 inches and 0.268 inches

**Internal Drive Style:**

Torx

**End Application:**

F-22 raptor (emd)

**Material Accommodated Thickness:**

0.718 inches

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

15539 pounds per square inch

**Product Name:**

Screw assembly panel

**Material:**

Nickel alloy 718

**Material Specification:**

Ms 5652 national std/spec single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Ms qq-p-35 national std/spec single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0