

View Online at <https://aerobasegroup.com/nsn/5305-01-538-4369>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.443 inches and 0.510 inches

**Fastener Length:**

Between 0.765 inches and 0.812 inches

**Head Style:**

Flat countersunk undercut

**Head Diameter:**

Between 0.502 inches and 0.507 inches

**Head Height:**

Between 0.071 inches and 0.073 inches

**Grip Diameter:**

Between 0.2490 inches and 0.2495 inches

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 0.302 inches and 0.322 inches

**Thready Qty Per Inch (tpi):**

28

**Countersink Angle:**

Between 99.5 degrees and 100.5 degrees

**Surface Finish:**

32.0 microinches threads

**Special Features:**

Furnished with one o-ring seal. Shank and threads have dry film lubricant applied, reply code lbg000 not listed this fiig

**Material:**

Titanium alloy

**Material Specification:**

Nas621 comp 6al-4v assn standard single material response or ams4928 assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0