

View Online at <https://aerobasegroup.com/nsn/5305-01-539-3977>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.469 inches

**Fastener Length:**

1.219 inches

**Head Style:**

Fillister countersunk

**Head Diameter:**

Between 0.389 inches and 0.394 inches

**Head Height:**

Between 0.070 inches and 0.074 inches

**Grip Diameter:**

Between 0.248 inches and 0.249 inches

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.250 inches

**Grip Length:**

0.750 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Product Name:**

Screw-close tolerance 100 degrees countersunk reduced head, hi-torque, non magnetic cres, ivd aluminum coated

**Special Features:**

Lubricant- cetyl alcohol

**Material:**

Nickel alloy 718

**Material Specification:**

Ams 5662 national std/spec single material response

**Surface Treatment:**

Aluminum

**Surface Treatment Specification:**

Mil-dtl-83488 type 2 cls 3 national std/spec single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-dtl-83488 spec.