

View Online at <https://aerobasegroup.com/nsn/5305-01-539-5850>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.531 inches

Fastener Length:

1.156 inches

Head Style:

Flat countersunk

Head Diameter:

0.429 inches

Grip Diameter:

Between 0.311 inches and 0.312 inches

Internal Drive Style:

High-torque

Thread Diameter:

0.312 inches

Grip Length:

0.625 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

125000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Product Name:

Screw-close tolerance 100 degrees countersunk reduced head, hi-torque, non magnetic cres, ivd aluminum coated

Special Features:

Lubricant- cetyl alcohol

Material:

Nickel alloy 718

Material Specification:

Ams 5662 national std/spec single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Mil-dtl-83488 type 2 cls 3 national std/spec single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-dtl-83488 spec.