NSN 5305-01-541-5249

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-541-5249

3a Fread Direction: Right-hand Thread Length: 0.045 inches Bastener Length: Between 0.780 inches and 0.810 inches Head Style: Fillister countersunk Head Height: 0.015 inches O.015 inches Spline Major Diameter: 0.221 inches Grip Dameter: 0.221 inches Between 0.249 inches and 0.250 inches Internal Drive Style: Torx Brighter aincraft (f180/f) Thread Diameter: 0.250 inches Orip Length: 0.250 inches Chip Length: 0.250 inches Drive Style: 230 Between 90. degrees and 100.0 degrees Product Name: (inavy) screw, close tolerance Matrial: Starles steel Starles steel Starles steel Starles steel Starles steel Starles steel Starles steel stesigneric: Unidf Measure:	Thread Class:			
Thread Direction: Right-hand Thread Length: 0.045 inches Fastener Length: Between 0.780 inches and 0.810 inches Head Style: Fillister countersunk Head Height: 0.015 inches Spline Major Diameter: 0.221 inches Spline Major Diameter: 0.221 inches Grip Diameter: Between 0.249 inches and 0.250 inches Internal Drive Style: Torx End Application: Fighter aircraft (f18e/f) Thread Diameter: 0.250 inches Grip Length: 0.250 inches Curteersink Angle: Between 99.0 degrees and 10.0 degrees Freaduct Angle: Starlaes Steel Surfae Treatment: Auminum Thread Steel Striae Steel Starlaes Steel Curteersink Curteersink Angle: Curteersink				
Right-hand Thread Length: 0.045 inches Fastener Length: Between 0.780 inches and 0.810 inches Head Style: Fillister countersunk Head Height: 0.015 inches Spline Major Diameter: 0.221 inches Grip Diameter: Between 0.249 inches and 0.250 inches Internal Drive Style: Torx End Application: Fighter aircraft (118e/f) Thread Diameter: 0.250 inches Grip Length: 0.260 inches Thread VP Per Inch (tpi): 28 Countersink Angle: Between 99.0 degrees and 10.0 degrees Product Name: (inavy) screw, close tolerance Material: Stainless steel Surface Treatment: Aurinium Thread Steine Designator: Unif Measure: Unif Measure: Tor				
Thread Length: 0.045 inches Fastener Length: Between 0.780 inches and 0.810 inches Head Style: Fillister countersunk Head Height: 0.015 inches Spline Major Diameter: 0.221 inches Grip Diameter: 0.221 inches Grip Diameter: 0.221 inches Between 0.249 inche and 0.250 inches Internal Drive Style: Torx End Application: Fighter aircraft (f18e/f) Thread Diameter: 0.250 inches Grip Length: 0.250 inches Countersink Angle: 28 Detween 99.0 degrees and 100.0 degrees Product Name: (inavy) screw, close tolerance Materiai: Stainless steel Stainless steel Stainless steel Unif Measure: Unif Measure: Unif Measure: Unif Measure: Thread Diameter: Unif Measure:				
0.045 inches Fastener Length: Between 0.780 inches and 0.810 inches Head Style: Fillister countersunk Head Height: 0.015 inches Spline Major Diameter: 0.221 inches Grip Diameter: 0.221 inches Grip Diameter: 0.221 inches Countersunk and 0.250 inches Internal Drive Style: Torx End Application: Fighter aircraft (18.6/7) Thread Diameter: 0.250 inches Grip Length: 0.250 inches Countersink Angle: Between 90.0 degrees and 100.0 degrees Product Name: (inavy strew, close tolerance Material: Stainless steel Surface Treatment: Auminum Thread Series Designator: Unif Shelf Life: Na				
Fastener Length: Between 0.780 inches and 0.810 inches Head Style: Fillister countersunk Head Height: 0.015 inches Spline Major Diameter: 0.221 inches Grip Diameter: 0.224 inches and 0.250 inches Internal Drive Style: Torx Pad Application: Fighter aircraft (118e/f) Thread Diameter: 0.250 inches Grip Length: 0.250 inches Thread Valle 0.250 inches Product Name: (inavy) screw, close tolerance Material: Stainless steel				
Between 0.780 inches and 0.810 inches Head Style: Fillister countersunk Head Height: 0.015 inches Splice Major Diameter: 0.221 inches Grip Diameter: 0.221 inches Grip Diameter: 1.221 inches Internal Drive Style: Torx End Application: Fighter aircraft (f18e/f) Thread Diameter: 0.250 inches Grip Length: 0.250 inches Grip Length: 0.250 inches Cuntersink Angle: Between 99.0 degrees and 100.0 degrees Product Name: (inavy) screw, close tolerance Material: Stainless steel Surface Treatment: Aluminum Thread Stell Surface Stell Surface Stell Surface Stell				
Head Style: Fillister countersunk Head Height: 0.015 inches Spline Major Diameter: 0.221 inches Grip Diameter: 0.221 inches Grip Diameter: Between 0.249 inches and 0.250 inches Internal Drive Style: Torx End Application: Fighter aircraft (118e/f) Thread Diameter: 0.250 inches Grip Length: 0.250 inches Grip Length: 0.250 inches Thread Diameter: 0.250 inches Grip Length: 0.250 inches Thready Qty Per Inch (tpi): 28 Countersink Angle: Between 99.0 degrees and 100.0 degrees Product Name: (invy) screw, close tolerance Material: Stainless steel Surface Treatment: Aluminum Thread Series Designator: Unjf Shelf Life: N/a Unit of Measure: To Demilitarization		10 inches		
Filister countersunk Head Height: 0.015 inches Spline Major Diameter: 0.221 inches Grip Diameter: 0.221 inches Grip Diameter: 0.220 inches and 0.250 inches Internal Drive Style: Torx End Application: Fighter aircraft (118e/f) Thread Diameter: 0.250 inches Grip Length: 0.250 inches Grip Length: 0.250 inches Countersink Angle: Between 99.0 degrees and 100.0 degrees Product Name: (inavy) screw, close tolerance Materia: Stainless steel Surface Treatment: Auminu Thread Series Designator: Unif Shelf Life: N/a Life Measure: Demilitarization:				
Head Height: 0.015 linches Spline Major Diameter: 0.221 linches Grip Diameter: Between 0.249 linches and 0.250 linches Internal Drive Style: Torx End Application: Fighter aircraft (118e/f) Thread Diameter: 0.250 linches Grip Length: 0.250 linches Thread Vi Per Inch (tpi): 28 Countersink Angle: Between 99.0 degrees and 100.0 degrees Product Name: (inavy) screw, close tolerance Material: Stainless steel Surface Treatment: Aluminum Thread Series Designator: Unif Sheft Life: Nra Dird Measure: Tore Interlistrization:				
0.015 inches Spline Major Diameter: 0.221 inches Grip Diameter: Between 0.249 inches and 0.250 inches Internal Drive Style: Torx End Application: Fighter aircraft (18e/f) Thread Diameter: 0.250 inches Grip Length: 0.250 inches Grip Length: 0.250 inches Thready Qty Per Inch (tpi): 28 Countersink Angle: Between 99.0 degrees and 100.0 degrees Product Name: (inavy screw, close tolerance Material: Stainless steel Surface Treatment: Aluminum Thread Series Designator: Unjf Shelf Life: Na Unit of Measure: Demilitarization:				
Spine Major Diameter: 0.221 inches Grip Diameter: Between 0.249 inches and 0.250 inches Internal Drive Style: Torx Torx End Application: Fighter aircraft (f18e/f) Thread Diameter: 0.250 inches Grip Length: 0.250 inches Thready Qty Per Inch (tpi): 28 Countersink Angle: Between 99.0 degrees and 100.0 degrees Product Name: (inavy) screw, close tolerance Material: Stainless steel Surface Treatment: Aluminum Thread Series Designator: Unjf Shelf Life: Na Unit of Measure: Demilitarization:				
O 221 inches Grip Diameter: Between 0.249 inches and 0.250 inches Internal Drive Style: Torx End Application: Fighter aircraft (118e/f) Thread Diameter: 0.250 inches Grip Length: 0.250 inches Thready Qty Per Inch (tpi): 28 Countersink Angle: Between 99.0 degrees and 100.0 degrees Product Name: (inavy) screw, close tolerance Material: Stainless steel Surface Treatment: Aluminum Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: 				
Grip Diameter: Between 0.249 inches and 0.250 inches Internal Drive Style: Torx End Application: Fighter aircraft (f18e/f) Thread Diameter: 0.250 inches Grip Length: 0.250 inches Thread Vap Per Inch (tpi): 28 Countersink Angle: Between 99.0 degrees and 100.0 degrees Product Name: (inavy) screw, close tolerance Material: Stainless steel Surface Treatment: Aluminum Thread Series Designator: Unif Shelf Life: N/a Detif Life: N/a Detif Life: N/a Detif Life: N/a Detif Life: Protect Drip Detif Life: N/a Drip Component Component Component Component Drip Component Component Component Drip				
Between 0.249 inches and 0.250 inches Internal Drive Style: Torx End Application: Fighter aircraft (118e/f) Thread Diameter: 0.250 inches Countersink Angle: Between 99.0 degrees and 100.0 degrees Product Name: (inavy) screw, close tolerance Material: Stainless steel Surface Treatment: Aluminum Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization:				
Internal Drive Style: Torx End Application: Fighter aircraft (f18e/f) Thread Diameter: 0.250 inches Grip Length: 0.250 inches Thready Qty Per Inch (tpi): 28 Countersink Angle: Between 99.0 degrees and 100.0 degrees Product Name: (inavy) screw, close tolerance Material: Stainless steel Surface Treatment: Aluminum Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization:		EQ inchoo		
Tox End Application: Fighter aircraft (f18e/f) Fighter aircraft (f18e/f) Thread Diameter: 0.250 inches Grip Length: 0.250 inches Thready Qty Per Inch (tpi): 28 Countersink Angle: Between 99.0 degrees and 100.0 degrees Product Name: (inavy) screw, close tolerance Material: Stainless steel Surface Treatment: Aluminum Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization:		JUTICITES		
End Application: Fighter aircraft (118e/f) Thread Diameter: 0.250 inches Grip Length: 0.250 inches Thready Qty Per Inch (tpi): 28 Countersink Angle: Between 99.0 degrees and 100.0 degrees Product Name: (inavy) screw, close tolerance Material: Stainless steel Surface Treatment: Aluminum Thread Series Designator: Unjf Sheff Life: N/a Unit of Measure: Demilitarization:				
Fighter aircraft (f18e/f) Thread Diameter: 0.250 inches Grip Length: 0.250 inches Thready Qty Per Inch (tpi): 28 Countersink Angle: Between 99.0 degrees and 100.0 degrees Product Name: (inavy) screw, close tolerance Material: Stainless steel Surface Treatment: Aluminum Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization:				
Thread Diameter: 0.250 inches Grip Length: 0.250 inches Thready Qty Per Inch (tpi): 28 Countersink Angle: Between 99.0 degrees and 100.0 degrees Product Name: (inavy) screw, close tolerance Material: (inavy) screw, close tolerance Material: Stainless steel Surface Treatment: Aluminum Thread Series Designator: Unif Sheff Life: N/a Unif Measure: Demilitarization:				
0.250 inches Grip Length: 0.250 inches Thready Qty Per Inch (tpi): 28 Countersink Angle: Between 99.0 degrees and 100.0 degrees Product Name: (inavy) screw, close tolerance Material: Stainless steel Surface Treatment: Aluminum Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization:				
Grip Length: 0.250 inches 0.250 inches Thready Qty Per Inch (tpi): 28 Countersink Angle: Between 99.0 degrees and 100.0 degrees Product Name: (inavy) screw, close tolerance Material: Stainless steel Surface Treatment: Aluminum Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization:				
0.250 inches Thready Qty Per Inch (tpi): 28 Countersink Angle: Between 99.0 degrees and 100.0 degrees Product Name: (inavy) screw, close tolerance Material: Stainless steel Surface Treatment: Aluminum Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization:				
Thready Qty Per Inch (tpi): 28 Countersink Angle: Between 99.0 degrees and 100.0 degrees Product Name: (inavy) screw, close tolerance Material: (inavy) screw, close tolerance Material: Stainless steel Surface Treatment: Aluminum Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization:				
28 Countersink Angle: Between 99.0 degrees and 100.0 degrees Product Name: (inavy) screw, close tolerance Material: Stainless steel Stainless steel Surface Treatment: Aluminum Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization:				
Countersink Angle: Between 99.0 degrees and 100.0 degrees Product Name: (inavy) screw, close tolerance Material: Stainless steel Stainless steel Surface Treatment: Aluminum Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: 				
Between 99.0 degrees and 100.0 degrees Product Name: (inavy) screw, close tolerance Material: Stainless steel Surface Treatment: Aluminum Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization:				
Product Name: (inavy) screw, close tolerance Material: Stainless steel Surface Treatment: Aluminum Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization:) 0 degrees		
(inavy) screw, close tolerance Material: Stainless steel Surface Treatment: Aluminum Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization:		.o degrees		
Material:Stainless steelSurface Treatment:AluminumThread Series Designator:UnjfShelf Life:N/aUnit Of Measure:Demilitarization:				
Stainless steel Surface Treatment: Aluminum Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization:				
Surface Treatment: Aluminum Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization:				
Aluminum Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization:				
Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization:				
Unjf Shelf Life: N/a Unit Of Measure: Demilitarization:				
Shelf Life: N/a Unit Of Measure: Demilitarization:				
N/a Unit Of Measure: Demilitarization:				
Unit Of Measure: Demilitarization:				
 Demilitarization:				
Demilitarization:				
	No			

NSN 5305-01-541-5249

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0

