

View Online at <https://aerobasegroup.com/nsn/5305-01-541-5356>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.219 inches

**Fastener Length:**

0.500 inches

**Head Style:**

Double chamfer

**Head Diameter:**

0.438 inches

**Head Height:**

0.125 inches

**Shoulder Diameter:**

0.305 inches all shoulders and 0.315 inches all shoulders

**Shoulder Length:**

0.281 inches all shoulders

**Locking Feature:**

Pellet all shoulders

**Internal Drive Style:**

Hexagon

**End Application:**

Escape truck flood valve on nssn class sub

**Thread Diameter:**

0.312 inches

**Width Across Flats:**

0.187 inches

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

110000 pounds per square inch

**Shoulder Shape:**

Round all shoulders

**Product Name:**

Retaining screw

**Special Features:**

Locking pellet is located 0.172 inch from runout of thread on shoulder

**Material:**

Plastic nylon locking feature

**Material Specification:**

Qq-s-763, cl 316, cd b federal specification single material response fastener

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0