NSN 5305-01-541-6213

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-541-6213

View Online at https://aerobasegroup.com/nsn/5305-01-541-6213
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.352 inches and 0.400 inches
Fastener Length:
Between 0.612 inches and 0.652 inches
Head Style:
Hexagon
Head Height:
Between 0.109 inches and 0.141 inches
Width Between Flats:
Between 0.365 inches and 0.377 inches
Hole Diameter:
Between 0.046 inches and 0.056 inches
Internal Drive Style:
W/o internal drive
Thread Diameter:
0.138 inches
Hole Quantity:
1
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
32
Hole Configuration Style:
Hexagon flats
Product Name:
Bolt
Material:
Steel comp 4037 or steel comp 8630 or steel comp 8740 or steel comp 4140 or steel comp 8735 or steel comp 4130
Material Specification:
Nas-6812 national std/spec single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Ams-qq-p-416, type ii, class 2 assn standard single treatment response
Thread Series Designator:
Unjc
Shelf Life:
N/a

NSN 5305-01-541-6213

Shoulder Screw - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0