## NSN 5305-01-541-7497

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-541-7497 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.420 inches and 0.430 inches **Fastener Length:** Between 0.910 inches and 0.940 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.385 inches and 0.394 inches **Spline Major Diameter:** Between 0.154 inches and 0.156 inches **Grip Diameter:** 0.249 inches **Point Diameter:** 0.245 inches **Point Style:** Flat **Internal Drive Style:** Torx **End Application:** Aircraft **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi): 28 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Bolt, 100 degrees reduced head, gear drive recess **Special Features:** 125 ksi shear Material: Nickel alloy 718 **Thread Series Designator:** 

Unjf Shelf Life: N/a

## NSN 5305-01-541-7497

Close Tolerance Screw - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0