## NSN 5305-01-542-8805

Panel Screw Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-542-8805

Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 0.735 inches and 0.765 inches
Head Style:
Flat countersunk
Head Diameter:
0.280 inches
Internal Drive Style:
Torx
End Application:
F-22 raptor
Material Accommodated Thickness:
Between 0.365 inches and 0.385 inches
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Product Name:
Screw, edm slot 100* reduced flat head, six lobe recess
Material:
Iron alloy 660
Material Specification:
Ams5731 assn standard single material response or ams5737 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 assn standard single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

## NSN 5305-01-542-8805

Panel Screw Assembly - Page 2 of 2



Fiig:

A003b0