## NSN 5305-01-542-8808

Panel Screw Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-542-8808 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.922 inches and 0.952 inches **Head Style:** Flat countersunk **Head Diameter:** 0.280 inches **Internal Drive Style:** Torx **End Application:** F-22 raptor **Material Accommodated Thickness:** Between 0.490 inches and 0.510 inches **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Screw edm slot 100\* reduced flat head six lobe recess Material: Iron alloy 660 **Material Specification:** Ams5731 assn standard single material response or ams5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5305-01-542-8808

Panel Screw Assembly - Page 2 of 2



Fiig:

A003b0