

View Online at <https://aerobasegroup.com/nsn/5305-01-544-3898>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.617 inches

**Fastener Length:**

0.750 inches

**Head Style:**

Flat countersunk

**Spline Major Diameter:**

Between 0.220 inches and 0.223 inches

**Internal Drive Style:**

Torx

**End Application:**

V-22 aircraft

**Thread Diameter:**

0.312 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

9200 pounds per square inch

**Countersink Angle:**

100.0 degrees

**Criticality Code Justification:**

Agav

**Product Name:**

Screw, 100 degree flush head, full thread, 6 lobe recess

**Locking Feature Material:**

Plastic polyethylene or plastic polyamide

**Screw Material Specification:**

Ams5731 assn standard single material response or ams5732 assn standard single material response or ams5737 assn standard single material response or ams5835 assn standard single material response

**Locking Feature Material Specification:**

Nas-15981 assn standard all material responses

**Screw Surface Treatment:**

Passivate

**Screw Surface Treatment Specification:**

Ams2700method 1, type 2 assn standard single treatment response or ams2700method 1, type8, class1 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A500d0