3a

32

---

Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-545-8927



**Thread Class: Thread Direction: Right-hand Thread Length:** Between 0.219 inches and 0.312 inches Fastener Length: Between 0.281 inches and 0.312 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches Locking Feature: Patch **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish: 32.0 microinches bearing surface of head Material: Steel comp 4140 Material Specification: Mil-s-5626 military standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a Unit Of Measure:

## NSN 5305-01-545-8927

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.