NSN 5305-01-545-8928

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-545-8928

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.899 inches and 1.061 inches
Fastener Length:
Between 1.119 inches and 1.156 inches
Head Style:
Hexagon
Head Height:
Between 0.188 inches and 0.203 inches
Width Between Flats:
Between 0.492 inches and 0.502 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.375 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
Between 36.0 rockwell c and 40.0 rockwell c
Screw Material:
Stainless steel
Screw Material Specification:
Ams 5731 assn standard single material response or ams 5737 assn standard single material response
Screw Surface Treatment:
Passivate
Screw Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Bearing Surface Of Head Surface Finish:
63.0 microinches
Shank Surface Finish:
32.0 microinches
Thread Surface Finish:
32.0 microinches
Special Features:
Specific matl is cres - a286 (uns 66286)
Thread Series Designator:
Linif

Unjf

NSN 5305-01-545-8928

Machine Screw - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0