NSN 5305-01-548-6599

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-548-6599 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.338 inches **Fastener Length:** Between 2.073 inches and 2.103 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** Between 36.0 rockwell c and 40.0 rockwell c **Screw Material:** Steel comp 4340 and steel comp 8740 **Screw Material Specification:** Mil-s-5626 military specification 1st material response and mil-s-8844 military specification 2nd material response and mil-s-6049 military specification 3rd material response **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Qq-p-416, ty3cl2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1403 professional/industrial association standard Shelf Life: N/a

No

Unit Of Measure:

Demilitarization:

NSN 5305-01-548-6599

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-s-5626 spec.