NSN 5305-01-548-8644

Machine Screw - Page 1 of 2



| view Online at https://aerobasegroup.com/nsn/5305-01-548-8644 |
|---|
| Thread Class: |
| Ba |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 1.498 inches and 1.530 inches |
| Fastener Length: |
| Between 1.546 inches and 1.592 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| Between 0.125 inches and 0.140 inches |
| Width Between Flats: |
| Between 0.367 inches and 0.376 inches |
| nternal Drive Style: |
| Cross recess type ii |
| End Application: |
| Aircraft osprey v-22a |
| Thread Diameter: |
| 0.250 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Product Name: |
| Screw, hex head, cruciform recess |
| Screw Material: |
| Stainless steel |
| Screw Material Specification: |
| A286 cres (uns s66286) conforming to the chemistry of ams5731, ams5732, ams5737 or ams5853 mfr ref single material response |
| Screw Surface Treatment: |
| Passivate |
| Screw Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Jnjf |
| Specification Data: |
| 30205 - nas1802 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 5305-01-548-8644

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0