NSN 5305-01-549-9629

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-549-9629 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.276 inches **Fastener Length:** Between 1.011 inches and 1.041 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.328 inches and 0.385 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches **Grip Length:** 0.750 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Titanium alloy uns r54520 **Material Specification:** Nas 621, 6al-4v assn standard single material response **Surface Treatment:** Aluminum **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1153 professional/industrial association standard Shelf Life:

N/a

NSN 5305-01-549-9629

Close Tolerance Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0