NSN 5305-01-550-4069

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-550-4069 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.276 inches **Fastener Length:** Between 0.761 inches and 0.791 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **Grip Diameter:** Between 0.188 inches and 0.189 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Titanium alloy uns r54520 **Material Specification:** Nas5621, comp 6al-4v assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Mil-c-83438, ty2cl3 military specification single treatment response **Thread Series Designator:** Unjf Shelf Life: **Unit Of Measure:**

N/a
Unit Of Measure:
-Demilitarization:

NSN 5305-01-550-4069

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-c-83438 spec.