

View Online at <https://aerobasegroup.com/nsn/5305-01-554-4801>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.953 inches

Fastener Length:

2.265 inches

Head Style:

Flat countersunk

Head Diameter:

Between 1.262 inches and 1.272 inches

Grip Diameter:

0.624 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.625 inches

Grip Length:

1.312 inches

Width Across Flats:

Between 0.501 inches and 0.504 inches

Thready Qty Per Inch (tpi):

18

Countersink Angle:

100.0 degrees

Material:

Steel comp 4140 or steel comp 4340 or steel comp 8740

Material Specification:

Ams6382 assn standard single material response or mil-s-5626 military specification single material response or ams6484 assn standard single material response or ams6414 assn standard single material response or ams6415 assn standard single material response or mil-s-8844 military specification single material response or ams6322 assn standard single material response or mil-s-6049 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.