NSN 5305-01-554-4801



Close Tolerance Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-554-4801 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.953 inches **Fastener Length:** 2.265 inches **Head Style:** Flat countersunk **Head Diameter:** Between 1.262 inches and 1.272 inches **Grip Diameter:** 0.624 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.625 inches **Grip Length:** 1.312 inches Width Across Flats: Between 0.501 inches and 0.504 inches Thready Qty Per Inch (tpi): 18 **Countersink Angle:** 100.0 degrees Material: Steel comp 4140 or steel comp 4340 or steel comp 8740 **Material Specification:** Ams6382 assn standard single material response or mil-s-5626 military specification single material response or ams6484 assn standard single material response or ams6414 assn standard single material response or ams6415 assn standard single material response or mil-s-8844 military specification single material response or ams6322 assn standard single material response or mil-s-6049 military specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type ii, class 2 federal specification single treatment response **Thread Series Designator:**

Unjf Shel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

NSN 5305-01-554-4801

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.