

View Online at <https://aerobasegroup.com/nsn/5305-01-559-7742>

**Thread Direction:**

Right-hand

**Thread Length:**

Between 9.70 millimeters and 12.30 millimeters

**Fastener Length:**

Between 11.70 millimeters and 12.30 millimeters

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 9.74 millimeters and 10.00 millimeters

**Head Height:**

Between 5.85 millimeters and 6.00 millimeters

**Internal Drive Style:**

Hexagon

**End Application:**

Light armoured vehicle engineering variant

**Thread Diameter:**

6.0 millimeters

**Width Across Flats:**

Between 5.020 millimeters and 5.084 millimeters

**Min. Tensile Strength (psi):**

1220 megapascals

**Hardness Rating:**

38.0 rockwell c and 44.0 rockwell c

**Minimum Yield Strength:**

1100 megapascals

**Thread Pitch In Millimeters:**

1.0

**External Thread Tolerance Class:**

4g6g

**Material:**

Steel property class 12.9

**Surface Treatment:**

Zinc and chromate

**Surface Treatment Specification:**

Astmb633, type 2, class3 assn standard single treatment response

**Thread Series Designator:**

M

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A003b0