NSN 5305-01-561-0415

Machine Screw - Page 1 of 2

Color: Silver



View Online at https://aerobasegroup.com/nsn/5305-01-561-0415

| Thread Directions |
|---|
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.880 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| 0.073 inches |
| Width Between Flats: |
| 0.372 inches |
| Hole Diameter: |
| 0.051 inches |
| Internal Drive Style: |
| Cross recess type ii |
| End Application: |
| Np2000 propeller control; e2 hawkeye aircraft |
| Thread Diameter: |
| 0.250 inches |
| Hole Quantity: |
| 3 |
| Thready Qty Per Inch (tpi): |
| 28 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Product Name: |
| Hex head screw |
| Screw Material: |
| Iron alloy 660 |
| Screw Material Specification: |
| Ms5731 assn standard single material response and 5732 assn standard single material response and ms5731 assn standard single |
| material response |
| Bearing Surface Of Head Surface Treatment: |
| Cadmium |
| Head Surface Treatment: |
| Cadmium |
| Screw Surface Treatment: |
| Cadmium |
| Shank Surface Treatment: |
| Cadmium |
| Special Features: |
| Used to hold brush block assembly in place |

NSN 5305-01-561-0415

Machine Screw - Page 2 of 2



| Supplementary Features | Sı | ıppl | eme | ntary | / Fo | eatı | ires | 3: |
|------------------------|----|------|-----|-------|------|------|------|----|
|------------------------|----|------|-----|-------|------|------|------|----|

T.O. (fr)01-e2aaa-4-3

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0