Socket Head Cap Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-562-4509

3a Thr Rigi Thr 0.62 Fas Bett Hea Bett Hea Bett Hea Dat Chr 0.1 <sup>-1</sup> Wice Bett Thr 0.1 <sup>-1</sup> Wice Bett Thr 0.1 <sup>-1</sup> Ster Ster	ead Class: ead Direction: ht-hand ead Length: 25 inches itener Length: ween 0.595 inches and 0.625 inches ad Style: it chamfer ad Diameter: ween 0.176 inches and 0.183 inches ad Height: ween 0.108 inches and 0.112 inches ernal Drive Style: itagon ead Diameter: 12 inches ith Across Flats: ween 0.094 inches and 0.095 inches
Thr Rigi Thr 0.62 Fas Bett Hea Bett Hea Bett Hea Chr 0.1 <sup>-1</sup> Wice Bett Thr 0.1 <sup>-1</sup> Wice Bett Thr 0.1 <sup>-1</sup> Ster Ster	ht-hand ead Length: 25 inches 25 inches tener Length: ween 0.595 inches and 0.625 inches ad Style: t chamfer ad Diameter: ween 0.176 inches and 0.183 inches ad Height: ween 0.176 inches and 0.112 inches prnal Drive Style: tagon ead Diameter: 12 inches
Rigl Thr 0.62 Fas Bett Hea Bett Hea Bett Hea Chr 0.1 <sup>2</sup> Wice Bett Thr 40 Min 800 Mat Stee	ht-hand ead Length: 25 inches 25 inches tener Length: ween 0.595 inches and 0.625 inches ad Style: t chamfer ad Diameter: ween 0.176 inches and 0.183 inches ad Height: ween 0.176 inches and 0.112 inches prnal Drive Style: tagon ead Diameter: 12 inches
Thr 0.62 Fas Bett Hea Bett Hea Bett Inte Hex Thr 0.1 <sup>-1</sup> Wic Bett Thr 40 Min 800 Mat	ead Length: 25 inches 25 inches 25 inches and 0.625 inches 26 OSP5 inches and 0.625 inches 26 OSP5 inches and 0.625 inches 27 OSP5 inches and 0.625 inches 26 OSP5 Inches and 0.625 inches 27 OSP5 Inches and 0.625 inches 26 OSP5 Inches and 0.625 inches 27 OSP5 Inches and 0.625 inches 28 OSP5 Inches and 0.625 inches 29 OSP5 Inches and 0.625 inches 20
0.62 Fas Bett Hea Bett Hea Bett Inte Hex Thr 0.1 <sup>-1</sup> Wic Bett Thr 40 Min 800 Mat	25 inches 25 inc
Fas Bett Hea Bett Hea Bett Inte Hex Thr 0.1 <sup>-1</sup> Wic Bett Thr 40 Min 800 Mat	stener Length:   ween 0.595 inches and 0.625 inches   ad Style:   ad Style:   ad height:   ween 0.176 inches and 0.183 inches   ad Height:   ween 0.108 inches and 0.112 inches   straal Drive Style:   sagon   ead Diameter:   12 inches   tat Across Flats:
Bett Hea Flat Hea Bett Hea Inte Hea Thr 0.1 <sup>-1</sup> Wice Bett Thr 40 Min 800 Mat	ween 0.595 inches and 0.625 inches ad Style: a chamfer ad Diameter: ween 0.176 inches and 0.183 inches ad Height: ween 0.108 inches and 0.112 inches ernal Drive Style: agon eed Diameter: 12 inches ath Across Flats:
Hea Flat Hea Bet Hea Hea Thr 0.1 <sup>-1</sup> Wic Bet Thr 40 Min 800 Mat	ad Style: i chamfer ad Diameter: ween 0.176 inches and 0.183 inches ad Height: ween 0.108 inches and 0.112 inches ernal Drive Style: kagon ead Diameter: 12 inches th Across Flats:
Flat Hea Bet Hea Et Hea Thr 0.1 <sup>-1</sup> Wic Bet Thr 40 Min 800 Mat	ad Diameter: ad Diameter: ween 0.176 inches and 0.183 inches ad Height: ween 0.108 inches and 0.112 inches ernal Drive Style: kagon read Diameter: 12 inches ath Across Flats:
Hea Bett Hea Inte Hex Thr 0.1 <sup>2</sup> Wic Bett Thr 40 Min 800 Mat	ad Diameter: ween 0.176 inches and 0.183 inches ad Height: ween 0.108 inches and 0.112 inches ernal Drive Style: kagon ead Diameter: 12 inches th Across Flats:
Bett Hea Bett Inte Hex Thr 0.1 <sup>-1</sup> Wic Bett Thr 40 Min 800 Mat Stee	ween 0.176 inches and 0.183 inches ad Height: ween 0.108 inches and 0.112 inches ernal Drive Style: kagon ead Diameter: 12 inches ath Across Flats:
Hea Bet Inte Hex Thr 0.1 <sup>2</sup> Wic Bet Thr 40 Min 800 Mat	ad Height: ween 0.108 inches and 0.112 inches ernal Drive Style: kagon ead Diameter: 12 inches ath Across Flats:
Bett Inte Hex Thr 0.1 Wic Bett Thr 40 Min 800 Mat	ween 0.108 inches and 0.112 inches
Inter Hex Thr 0.1 <sup>1</sup> Wic Bett Thr 40 Min 800 Mat	ernal Drive Style: kagon ead Diameter: 12 inches Sth Across Flats:
Hex Thr 0.11 Wic Bet <sup>*</sup> Thr 40 Min 800 Mat	kagon read Diameter: 12 inches Ith Across Flats:
Thr 0.1 <sup>4</sup> Wic Bet Thr 40 Min 800 Mat	ead Diameter: 12 inches hth Across Flats:
0.14 Wice Bette Thr 40 Mine 800 Mate Stee	12 inches Ith Across Flats:
Wic Bet Thr 40 Min 800 Mat	Ith Across Flats:
Bet Thr 40 Min 800 Mat	
Thr 40 Min 800 Mat	ween 0.094 inches and 0.095 inches
40 Min 800 Mat	
Min 800 Mat	eady Qty Per Inch (tpi):
800 <b>Mat</b> Stee	
Mat Ste	a. Tensile Strength (psi):
Ste	00 pounds per square inch
	terial:
	el comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316
Sur	face Treatment:
Pas	ssivate
Thr	ead Series Designator:
Unc	
She	elf Life:
N/a	
Uni	t Of Measure:
 Der	nilitarization:
No.	
Fiig	
AOC	