## NSN 5305-01-562-5549

**Thread Class:** 

2a

Assembled Washer Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-562-5549



**Thread Direction:** Right-hand Fastener Length: Between 0.418 inches and 0.438 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.195 inches and 0.208 inches **Head Height:** Between 0.070 inches and 0.080 inches Washer Quantity: **Internal Drive Style:** Cross recess type ii **Thread Diameter:** 0.122 inches Thready Qty Per Inch (tpi): 40 **Secondary Washer Relationship To Primary Washer:** Not identical **Secondary Washer Style:** Flat **Primary Washer Outside Diameter:** Between 0.195 inches and 0.208 inches **Secondary Washer Outside Diameter:** Between 0.204 inches and 0.224 inches **Primary Washer Style:** Split helical ring **Primary Washer Material Thickness:** Between 0.031 inches and 0.047 inches **Secondary Washer Material Thickness:** Between 0.028 inches and 0.036 inches **Product Name:** Screw, pan head, phillips, double sems Color: Black Material: Steel property class 18.8 fastener **Surface Treatment:** 

Oxide

## NSN 5305-01-562-5549

Assembled Washer Screw - Page 2 of 2



Mil-dtl-13924. Cl 4 military specification single treatment response

**Thread Series Designator:** 

Unc

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-dtl-13924 spec.