NSN 5305-01-566-1432

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-566-1432 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.391 inches **Fastener Length:** Between 0.468 inches and 0.500 inches **Head Style:** Pan **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.105 inches and 0.115 inches Washer Quantity: **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 **Secondary Washer Relationship To Primary Washer:** Not identical **Secondary Washer Style:** Flat **Primary Washer Outside Diameter:** 0.296 inches **Secondary Washer Outside Diameter:** Between 0.370 inches and 0.390 inches **Primary Washer Style:** Split helical ring **Primary Washer Material Thickness:** 0.040 inches **Secondary Washer Material Thickness:** Between 0.013 inches and 0.019 inches **Product Name:** Screw, pan head, assembled washers, standard shoulder washer Material:

Stainless steel secondary washer

Material Specification:

Qq-s-763 federal specification single material response fastener

NSN 5305-01-566-1432

Assembled Washer Screw - Page 2 of 2



Surface Treatment:
Passivate
Surface Treatment Specification:
Ams-qq-p-35 assn standard single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0