

View Online at <https://aerobasegroup.com/nsn/5305-01-566-3493>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.391 inches

**Fastener Length:**

Between 0.468 inches and 0.500 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.306 inches and 0.322 inches

**Head Height:**

Between 0.105 inches and 0.115 inches

**Washer Quantity:**

2

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.164 inches

**Thready Qty Per Inch (tpi):**

32

**Secondary Washer Relationship To Primary Washer:**

Not identical

**Secondary Washer Style:**

Flat

**Primary Washer Outside Diameter:**

0.296 inches

**Secondary Washer Outside Diameter:**

Between 0.370 inches and 0.390 inches

**Primary Washer Style:**

Split helical ring

**Primary Washer Material Thickness:**

0.040 inches

**Secondary Washer Material Thickness:**

Between 0.013 inches and 0.019 inches

**Product Name:**

Screw, pan head, assembled washers, standard shoulder washer

**Color:**

Black

**Material:**

Stainless steel secondary washer

**Material Specification:**

Qq-s-763 federal specification single material response fastener

**Surface Treatment:**

Oxide

**Surface Treatment Specification:**

Mil-dtl-13924. Class 4 military standard single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-dtl-13924 spec.