NSN 5305-01-567-1466

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-567-1466

Thread Direction:	
Right-hand	
Thread Length:	
Between 11.7 millimeters and 12.3 millimeters	
Fastener Length:	
Between 11.7 millimeters and 12.3 millimeters	
Head Style:	
Undercut pan no. 2	
Head Diameter:	
Between 7.7 millimeters and 8.0 millimeters	
Head Height:	
Between 2.2 millimeters and 2.4 millimeters	
Internal Drive Style:	
Torque set	
End Application:	
1340-01-543-5696 rocket pod, 298 millimeter	
Thread Diameter:	
4.0 millimeters	
Min. Tensile Strength (psi):	
1100 megapascals	
Product Name:	
Screw machine, pan head, offset cruciform, a286 cres full thread	
Screw Material:	
Stainless steel	
Bearing Surface Of Head Surface Treatment:	
Passivate	
Head Surface Treatment:	
Passivate	
Screw Surface Treatment:	
Passivate	
Shank Surface Treatment:	
Passivate	
Bearing Surface Of Head Surface Treatment Specification:	
Qq-p-35 federal specification single treatment response	
Head Surface Treatment Specification:	
Qq-p-35 federal specification single treatment response	
Screw Surface Treatment Specification:	
Qq-p-35 federal specification single treatment response	
Shank Surface Treatment Specification:	
Qq-p-35 federal specification single treatment response	
Thread Series Designator:	
Mj	

NSN 5305-01-567-1466

Machine Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A500d0

