NSN 5305-01-567-9236

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-567-9236

view Online at https://aerobasegroup.com/hsh/5305-01-567-9236
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.276 inches
Fastener Length:
0.401 inches
Head Style:
Pan
Head Diameter:
Between 0.256 inches and 0.270 inches
Head Height:
Between 0.087 inches and 0.097 inches
Grip Diameter:
Between 0.136 inches and 0.137 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.138 inches
Grip Length:
0.125 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Material:
Titanium alloy uns r56400
Material Specification:
Ams 4967 assn standard single material response
Surface Treatment:
Aluminum
Surface Treatment Specification:
Mil-c-83488, tyii, cl3 military specification single treatment response
Thread Series Designator:
Unjc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Van damil/mli

Yes - demil/mli

NSN 5305-01-567-9236

Close Tolerance Screw - Page 2 of 2



Fiig: A003b0

Mil-std (military Standard):

Mil-c-83488 spec.