# NSN 5305-01-568-2079

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-568-2079

## Thread Direction:

Right-hand

Thread Length:

13.5 millimeters

## Fastener Length:

16.0 millimeters

## Head Style:

Flat countersunk

#### Head Diameter:

9.2 millimeters

#### Internal Drive Style:

Slot

#### **End Application:**

End item nsn: 2420-01-560-2306; interim vehicle mounted mine detection (ivmmd) mkiii system, husky

#### Thread Diameter:

5.0 millimeters

## Min. Tensile Strength (psi):

58000 pounds per square inch

# Hardness Rating:

71.0 rockwell b

#### **Thread Pitch In Millimeters:**

0.8

**External Thread Tolerance Class:** 

6h

#### **Countersink Angle:**

90.0 degrees

**Screw Material:** 

Steel

Bearing Surface Of Head Surface Treatment:

Zinc

# Head Surface Treatment:

Zinc

# Screw Surface Treatment:

Zinc

# Thread Series Designator:

м

#### Shelf Life:

N/a

#### Unit Of Measure:

---

# Demilitarization:

No

# NSN 5305-01-568-2079

Machine Screw - Page 2 of 2

Fiig: A500d0

