NSN 5305-01-569-1709

Close Tolerance Screw - Page 1 of 2



| Close Tolerance Screw - Page 1 of 2 |
|--|
| View Online at https://aerobasegroup.com/nsn/5305-01-569-1709 |
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.276 inches |
| Fastener Length: |
| 0.464 inches |
| Head Style: |
| Pan |
| Head Diameter: |
| Between 0.357 inches and 0.373 inches |
| Head Height: |
| Between 0.122 inches and 0.133 inches |
| Grip Diameter: |
| Between 0.188 inches and 0.189 inches |
| Internal Drive Style: |
| Offset cruciform (torque set) |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| 0.188 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Material: |
| Titanium alloy uns r56400 |
| Material Specification: |
| Ams 4967 assn standard single material response |
| Surface Treatment: |
| Aluminum |
| Surface Treatment Specification: |
| Mil-c-83488, ty ii, cl3 military specification single treatment response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Νο |
| Fiig: |
| A003b0 |
| |

NSN 5305-01-569-1709

Close Tolerance Screw - Page 2 of 2

Mil-std (military Standard):

Mil-c-83488 spec.

