Hexagon Head Cap Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-569-2699

| Thre | ead Direction: |
|------|--------------------------------------------|
| Righ | nt-hand |
| Thre | ead Length: |
| 40.0 | millimeters |
| Fast | tener Length: |
| 40.0 | millimeters |
| Hea | d Style: |
| Hex | agon |
| Hea | d Height: |
| 10.0 | millimeters |
| Wid | th Between Flats: |
| 24.0 | millimeters |
| End | Application: |
| 2420 | 0-01-560-2306 tractor, wheeled, high speed |
| Thre | ead Diameter: |
| 16.0 | millimeters |
| Min. | Tensile Strength (psi): |
| 1160 | 000 pounds per square inch |
| Hare | dness Rating: |
| 21.0 | rockwell c |
| Thre | ead Pitch In Millimeters: |
| 2.0 | |
| Exte | ernal Thread Tolerance Class: |
| 6h | |
| Pro | duct Name: |
| Сар | screw |
| Mate | erial: |
| Stee | 9 |
| Surf | ace Treatment: |
| Zinc | |
| Thre | ead Series Designator: |
| М | |
| She | If Life: |
| N/a | |
| Unit | Of Measure: |
| | |
| Den | nilitarization: |
| No | |
| Fiig | |
| A00 | 3b0 |