

View Online at <https://aerobasegroup.com/nsn/5305-01-570-7502>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.750 inches

**Fastener Length:**

0.750 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.473 inches and 0.492 inches

**Head Height:**

Between 0.162 inches and 0.175 inches

**Internal Drive Style:**

Cross recess type 1

**End Application:**

1520-01-355-8250 helicopter, attack

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Product Name:**

Screw, machine, pan head

**Screw Material:**

Steel comp 4140

**Screw Material Specification:**

Mil-s-5626 military specification single material response

**Head Surface Treatment:**

Cadmium

**Screw Surface Treatment:**

Cadmium

**Screw Surface Treatment Specification:**

Qq-p-416, type ii. Class 2 federal specification single treatment response

**Thread Series Designator:**

Unjef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A500d0

**Mil-std (military Standard):**

Mil-s-5626 spec.