## NSN 5305-01-571-0218



Assembled Washer Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-571-0218 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.860 inches **Fastener Length:** 1.000 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.132 inches Washer Quantity: **Internal Drive Style:** Cross recess type 1 **End Application:** An/ttc-6 (v) 1, 2 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Secondary Washer Relationship To Primary Washer:** Not identical **Secondary Washer Style: Primary Washer Outside Diameter:** 0.337 inches **Secondary Washer Outside Diameter:** Between 0.433 inches and 0.453 inches **Primary Washer Style:** Split helical ring **Primary Washer Material Thickness:** 0.047 inches **Secondary Washer Material Thickness:** Between 0.029 inches and 0.035 inches **Product Name:** 

Screw, pan head, assembled washers, standard shoulder washer

Material:

Stainless steel secondary washer

## NSN 5305-01-571-0218

Assembled Washer Screw - Page 2 of 2



Material Specification:
Qq-s-763 federal specification single material response fastener
Surface Treatment:
Passivate
Surface Treatment Specification:
Ams-qq-p-35 assn standard single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0