NSN 5305-01-571-6278

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-571-6278 **Thread Class:** 2a **Thread Direction:** Right-hand Fastener Length: 0.875 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.132 inches Washer Quantity: **Internal Drive Style:** Cross recess type iii **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Primary Washer Style:** Flat **Primary Washer Material Thickness:** Between 0.029 inches and 0.035 inches **Product Name:** Screw, pan head, assembled washers, standard shoulder washer Material: Stainless steel **Material Specification:** Flat washer-ams-qq-s-763a class 302 condition b or class 304 condition a, or class 384. Consition a assn standard 1st material response and lock washer-nas-35338 national std/spec 2nd material response and screw iaw ms51957 military specification 3rd material response **Surface Treatment: Passivate Surface Treatment Specification:** Ams-qq-p-35 assn standard single treatment response **Supplementary Features:** Washers not identical/primary washer outside diameter 0.433 to 0.453 in **Thread Series Designator:**

Unf

N/a

Shelf Life:

Unit Of Measure:

NSN 5305-01-571-6278

Assembled Washer Screw - Page 2 of 2



em			

No

Fiig:

A003b0

Mil-std (military Standard):

spec.