NSN 5305-01-571-7799

Machine Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-571-7799

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.875 inches
Fastener Length:
0.0875 inches
Head Style:
Pan
Head Diameter:
Between 0.473 inches and 0.492 inches
Head Height:
Between 0.162 inches and 0.750 inches
Internal Drive Style:
Cross recess type 1
End Application:
Mrap - unique nsn - rg33 cat i
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
20
20
Min. Tensile Strength (psi):
Min. Tensile Strength (psi):
Min. Tensile Strength (psi): 60000 pounds per square inch
Min. Tensile Strength (psi): 60000 pounds per square inch Product Name:
Min. Tensile Strength (psi): 60000 pounds per square inch Product Name: Screw, machine
Min. Tensile Strength (psi): 60000 pounds per square inch Product Name: Screw, machine Screw Material:
Min. Tensile Strength (psi): 60000 pounds per square inch Product Name: Screw, machine Screw Material: Steel comp 1010
Min. Tensile Strength (psi): 60000 pounds per square inch Product Name: Screw, machine Screw Material: Steel comp 1010 Screw Material Specification:
Min. Tensile Strength (psi): 60000 pounds per square inch Product Name: Screw, machine Screw Material: Steel comp 1010 Screw Material Specification: 66 federal standard all material responses
Min. Tensile Strength (psi): 60000 pounds per square inch Product Name: Screw, machine Screw Material: Steel comp 1010 Screw Material Specification: 66 federal standard all material responses Screw Surface Treatment:
Min. Tensile Strength (psi): 60000 pounds per square inch Product Name: Screw, machine Screw Material: Steel comp 1010 Screw Material Specification: 66 federal standard all material responses Screw Surface Treatment: Zinc
Min. Tensile Strength (psi): 60000 pounds per square inch Product Name: Screw, machine Screw Material: Steel comp 1010 Screw Material Specification: 66 federal standard all material responses Screw Surface Treatment: Zinc Screw Surface Treatment Specification:
Min. Tensile Strength (psi): 60000 pounds per square inch Product Name: Screw, machine Screw Material: Steel comp 1010 Screw Material Specification: 66 federal standard all material responses Screw Surface Treatment: Zinc Screw Surface Treatment Specification: Qq-p-416 type 2 cl 3 federal specification single treatment response
Min. Tensile Strength (psi): 60000 pounds per square inch Product Name: Screw, machine Screw Material: Steel comp 1010 Screw Material Specification: 66 federal standard all material responses Screw Surface Treatment: Zinc Screw Surface Treatment Specification: Qq-p-416 type 2 cl 3 federal specification single treatment response Thread Series Designator:
Min. Tensile Strength (psi): 60000 pounds per square inch Product Name: Screw, machine Screw Material: Steel comp 1010 Screw Material Specification: 66 federal standard all material responses Screw Surface Treatment: Zinc Screw Surface Treatment Specification: Qq-p-416 type 2 cl 3 federal specification single treatment response Thread Series Designator: Unc
Min. Tensile Strength (psi): 60000 pounds per square inch Product Name: Screw, machine Screw Material: Steel comp 1010 Screw Material Specification: 66 federal standard all material responses Screw Surface Treatment: Zinc Screw Surface Treatment Specification: Qq-p-416 type 2 cl 3 federal specification single treatment response Thread Series Designator: Unc Specification Or Standard:
Min. Tensile Strength (psi): 60000 pounds per square inch Product Name: Screw, machine Screw Material: Steel comp 1010 Screw Material Specification: 66 federal standard all material responses Screw Surface Treatment: Zinc Screw Surface Treatment Specification: Qq-p-416 type 2 cl 3 federal specification single treatment response Thread Series Designator: Unc Specification Or Standard: 3 type

NSN 5305-01-571-7799

Machine Screw - Page 2 of 2

Demilitarization:

Yes - demil/mli

Fiig:

A500d0

